



DECLARATION OF PERFORMANCE

MoreFlex Rapid S1 Grey

DOP No. 028

Unique identification code of the product-type:

MoreFlex Rapid S1 Grey

Intended use/es:

Improved fast setting deformable cementitious adhesive with reduced slip

Manufacturer:

Kelmores Ltd, The Dell, Berry Way, Chorley, PR7 6RA

System/s of AVCP:

System 3

System 4 for reaction to fire

Harmonised standard:

BS EN 12004-1:2017

Notified body:

TZUS No. 1020

Declared Performance/s:

Essential Characteristics	Performance
Reaction to fire	Class E
Bond strength as:	
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer by:



R+D Manager

Note: Information on the content of substances concerning the Registration, Evaluation, Authorisation, and Restriction of Chemicals (UK REACH), is indicated in the safety data sheet available on the website together with this current declaration of performance.