

TECHNICAL DATA SHEET

Waterproof Tape

20/08/26

Self-adhesive tape for creating a waterproof seal

Key Features

- Use in conjunction with Kelmore's Waterproofing Paste or waterproof tile backer boards
- Use to form a waterproof seal at joints, junctions and fixing points
- Butyl-rubber backing forms a strong bond
- Centrally split, removable backing paper facilitates application in angled junctions



Technical Information

Pack size	10m
Product type	Self-adhesive, waterproof tape
Tape dimensions	Length 10m Width 100mm Thickness 1mm
Colour	Grey

Areas of Use

Walls and Floors	Interior	Domestic and Commercial	Showers	Wet Rooms
------------------	----------	-------------------------	---------	-----------

Background and Surface Preparation

Backgrounds must be sufficiently dry and strong enough to carry the total weight being applied. Ensure falls in the substrate have the required gradients and all drainage is capable of efficiently handling the expected rate of water flow. All surfaces must be clean, sound, flat and free from contaminants that could impair adhesion.

Application

Kelmore Waterproof Tape has a centrally split, removable backing paper which allows staged removal for ease of application.

- Pre-cut the tape to size using scissors or a utility knife.
- Peel off part of the split paper backing, place over the joint, junction or fixing point and press firmly into place.
- Continue to remove the paper backing whilst firmly pressing and smoothing the tape into place until all the paper has been removed and the tape is smooth and strongly adhered to the background.

Notes:

- Waterproof Tape must only be used on dry, internal backgrounds and is not suitable in areas subject to rising damp or negative water pressure.
- Do not use in areas of total water immersion such as swimming pools and storage tanks.

Storage: Store in unopened packaging, off the ground, and in cool, dry conditions.

BS & EN Standards: Product should be used in accordance with the requirements of the relevant British and European Standards.

All the information supplied by Kelmor Ltd is offered in good faith and is derived from the company's combined knowledge, experience and testing. Without prior notice, due to on-going research and development, the information we offer can be updated at any time. Kelmor's products are developed, tested and manufactured to consistently high standards, however, we accept no liability for any loss or damage which may arise from factors outside of our control, such as site conditions and/or the execution of the work.

Kelmor Ltd, The Dell, Berry Way, Chorley, PR7 6RA
Tel: +44 (0)1257 830511 Web: www.kelmor.co.uk
Email: technical@kelmor.co.uk

Supplied in the EU by: Kelmor EU Ltd
Tel: +353 (1)263 5959 Web: www.kelmor.ie
Email: technical@kelmor.co.uk