

DECLARATION OF PERFORMANCE

MoreTrade Rapid Flex Grey
DOP No. 045

Unique identification code of the product-type:
MoreTrade Rapid Flex Grey

Intended use/es:
Improved fast setting cementitious adhesive with reduced slip

Manufacturer:
Kelmores Ltd, The Dell, Berry Way, Chorley, PR7 6RA

System/s of AVCP:
System 3
System 4 for reaction to fire

Harmonised standard:
BS EN 12004-1:2017

Notified body:
Lucideon No. 1289

Declared Performance/s:

Essential Characteristics	Performance
Reaction to fire	Class E
Bond strength as:	
Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
Durability for:	
Tensile adhesion strength after heat ageing	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after water immersion	$\geq 1,0 \text{ N/mm}^2$
Tensile adhesion strength after freeze-thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	See SDS

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom in respect of Great Britain under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

 R+D Manager	Note: Information on the content of substances concerning the Registration, Evaluation, Authorisation, and Restriction of Chemicals (UK REACH), is indicated in the safety data sheet available on the website together with this current declaration of performance.
--	--